

## Technical data sheet

# UL-340S-230-045-S2/8Fx

## For F&S damper according to UL555

### Description

**Spring- return fire Actuator including external tripping device for fire and smoke dampers of 90° angle of rotation to be used in HVAC installations.**

- **Torque Motor** 5 Nm [45 in-lb]
- **Torque Spring** 5 Nm [45 in-lb]
- **Nominal Voltage** 230 VAC/DC
- **Control** 2 Point
- **Auxiliary switch** 2x fixed, not adjustable
- **Damper shaft adaption** form closure 8 mm [0.32 in] (8F 8)  
form closure 10 mm [0.40 in] (8F10)  
form closure 12 mm [0.48 in] (8F12)



### Technical data

<b>Nominal voltage</b>	Nominal voltage	230 VAC (50/60Hz), 230 VDC
	Nominal voltage range	85...265 VAC
	Power consumption motor (motion)	6 W
	Power consumption standby (end position)	1,5 W
	Wire sizing	12 VA
	Control	2 Point
	Position feedback	-
	Auxiliary switch	2 x SPDT (AgAu)
	Contact load	1 mA...5 (2,5) A, 5 VDC...250 VDC
	Switching point	5° / 80° @ -5°...+90°
<b>Functional data</b>	Connection Motor	Cable 1000 mm [3,3 ft], 2 x AWG 18
	Connection Auxiliary switch	Cable 1000 mm [3,3 ft], 6 x AWG 18
	Connection GUAC	-
	Torque Motor	>5 Nm [45 in-lb]
	Torque Spring	>5 Nm [45 in-lb]
	Synchronised speed	±5%
	Direction of rotation	selected by mounting
	Manual override	Manual operation
	Angle of rotation	-5°...max.+90°
	Running time Motor	<30 s / 90°
	Running time Spring	<10 s / 90°
	Sound power level Motor	<45 dB(A)
	Sound power level Spring	<65 dB(A)
	Damper coupling	form closure 8 mm [0.32 in] (8F 8) form closure 10 mm [0.40 in] (8F10) form closure 12 mm [0.48 in] (8F12)
	Position indication	mechanical with pointer
	Service life	>60.000 cycles (-5°...+90°...-5°)

## Technical data

<b>Safety</b>	Protection class	II (double insulation)
	Degree of protection	IP54 [NEMA 2]
	UL	UL 873 UL 94 5V
	Mode of operation	Typ 1.AA B (EN60730-2-14)
	Rated impulse voltage	4 kV (EN60730-1)
	Control pollution degree	2 (UL 840)
	Ambient temperature normal operation	-30°C...+50°C [-22°F...+122°F]
	Storage temperature	-30°C...+50°C [-22°F...+122°F]
	Ambient humidity	5...95% r.F., not condensing (EN 60730-1)
	Maintenance	maintenance-free
<b>Dimensions/ Weight</b>	Dimensions	145 x 75 x 70 mm [5.71 x 2.95 x 2.76 in]
	Weight	ca. 1.200g [2.65 lb]

## Operating mode / Properties

### Operating mode

Through connecting the power supply to blk+red, the actuator moves to position 1 while the pre-tensioned spring is wound up the same time. If the power supply is interrupted the actuator is moving back to position 0 by the spring power. The actuator is still maintaining the minimum torque at the damper spindle.

The damper actuators running time is adapted to come closer to the needs of UL555/UL555S requirements.

The actuator is overload-proof and requires no end switches. It automatically stops when the end stop is reached.

### Direct mounting

Simple direct mounting on the damper spindle with formlock, supplied with anchoring supports to prevent the actuator from rotating.



### Signaling

The two integrated auxiliary switches are activated at the fixed switching positions (< 5° and > 80°). The damper position can be checked by the mechanical pointer.

### Manual override

The actuator can be operated only manually while the power supply is off. The supplied lever is to open and lock the damper position. The lock stays until the power supply is put on.

Connection / Safety remarks



**Safety remarks**

- Attention mains voltage
- The actuator is not allowed to be used outside the specified field of application, especially in airplanes.
- In may only be installed by suitably trained personnel. Any legal regulations or regulations issued by authorities must be observed during assembly.
- The device may only be opened at the manufacturer's site.
- When calculating the required torque, the specifications supplied by the damper manufacturers (cross- section, design, installation site), and the air flow conditions must be observed.
- The actuator is not allowed to be disposed of as household refuse. All locally valid regulations and requirements must be observed.

Technical drawing

